



CONTACT

Website:
crosswind-tire.com



Catalog



Web



@crosswindtire



@crosswind_tire



PASSENGER CAR & LIGHT TRUCK TIRE CATALOG



Explore the Dream

crosswind-tire.com

245/50R20 102W

CROSSWIND

M+S

MAX. LOAD 850kg (1874lbs)
MAX. PRESS 350kPa (5.2psi)

PLIES: TREAD 2 POLYESTER + 2 STEEL + 1 POLYAMIDE
SIDEWALL 2 POLYESTER

Explore the Dream

TABLE OF CONTENTS

COMPANY INTRODUCTION

COMPANY INTRODUCTION03

GLOBAL LAYOUT07

PRODUCT INTRODUCTION

Ultra Sport+11

CrossWind HP⁰¹⁰ PLUS15

Crosswind HT²19

TrailTraxx23

Rugged Traxx27

Replacement Market Tires Warranty Manual31

An aerial photograph of a multi-lane highway interchange with several overpasses. In the upper left corner, a large, detailed image of a Crosswind tire is overlaid. The tire is black with a multi-spoke alloy wheel. The sidewall of the tire features the 'CROSSWIND' brand name in large, bold, white letters. Above it, the specifications '245/50R20 102W' are visible. Below the brand name, smaller text reads 'M+S', 'MAX. LOAD 850KG (1874lbs)', and 'MAX. PRESS 360KPa (5.1psi)'. At the very bottom of the sidewall, it says 'PLIES: TREAD 2 POLYESTER + 2 STEEL + 1 POLYAMIDE' and 'SIDEWALL 2 POLYESTER'.

COMPANY INTRODUCTION

Founded in 1975, Shandong Linglong Tyre Co., Ltd. has grown into one of the world's leading tire manufacturers, delivering innovative and high-performance tire solutions to customers across more than 170 countries. As a vertically integrated manufacturer, Linglong combines advanced research and development, intelligent manufacturing, global supply chain capabilities, and comprehensive customer support to meet the evolving needs of the automotive and commercial transportation industries.

crosswind-tire.com

Our retail network consists of

200,000

outlets globally, promoting our brand reputation and customer loyalty through our reliable product quality and excellent customer service.

Sold in over 170 countries worldwide, Linglong Tire is a trusted global manufacturer supplying original equipment (OE) tires to more than 200 vehicle production facilities for over 70 leading automotive brands. With more than 300 million OE tires delivered globally, Linglong's proven engineering, quality, and manufacturing expertise provide distributors, dealers, fleets and OEM partners across the globe with reliable, high-performance tire solutions backed by global scale and consistent supply.

Linglong's brand value reached

17.85

Billion dollars in 2026

Linglong has sponsored over

100

Sports events and teams worldwide

SPONSORING SOME OF THE BIGGEST NAMES IN SPORTS

Such as Real Madrid CF and Chelsea FC, to enhance its brand awareness and influence.



GLOBAL LAYOUT




R&D Center in the United States


R&D Center in Germany

Serbia


Linglong International
Europe d.o.o.Zrenjanin


Linglong International
Tyre(Thailand)Co.,Ltd

Open R&D Innovation System

3

Countries



8

R&D Centers



1500+

Authorized Patents



2000+

Technical Team



Global Strategic Layout

Linglong Tire's global manufacturing network is built on a strategic "Globalization + Regionalization + Localization" approach, enabling the company to efficiently serve customers across key markets worldwide. With multiple production facilities throughout China and international manufacturing hubs in Thailand and Serbia, Linglong delivers scalable production capacity, reliable supply chain performance, and localized market support to distributors, dealers, fleets, and OEM partners around the world.

Production Bases Outside China

- Linglong International Tyre (Thailand) Co., Ltd.
- Linglong International Europe d.o.o. Zrenjanin
- Under continuous evaluation.

Production Bases in China

- Jilin Linglong Tyre Co., Ltd.
- Shandong Linglong Tyre Co., Ltd.
- Dezhou Linglong Tyre Co., Ltd.
- Hubei Linglong Tyre Co., Ltd.
- Guangxi Linglong Tyre Co., Ltd.



Tire Portfolio for Every Application

Explore our product portfolio to find the tire best suited for your vehicle, operating conditions, and performance requirements.



	Ultra High Performance	High Performance	Highway Terrain	All-Terrain	Rugged Terrain
	ULTRA SPORT+ <i>Ultra High Performance</i>	HP⁰¹⁰ PLUS <i>High Performance</i>	CROSSWIND H/T² <i>Highway Terrain Tire</i>	TRAILTRAXX <i>All-Terrain Tire</i>	RUGGED TRAXX <i>Rugged Terrain Tire</i>
					
Sports Car	☒	☐			
Luxury Performance Touring	☐	☒			
Car & Minivan		☒			
CUV & SUV		☐	☒	☐	☐
Light Truck & Pickup			☐	☒	☒
Light Commercial				☐	☐

☒ Best match ☐ Secondary match



Explore the Dream.

Ultra Sport+

Ultra High Performance



Exceptional Handling

The asymmetric tread pattern provides superior grip and braking performance

3D sipe design minimizes tread block movement, enabling excellent control



Confident Driving in All Seasons

High-density siping enables improved wet and snow performance



Ultra High Performance

ULTRA SPORT+

WET BRAKING	★★★★★	RIDE COMFORT	★★★★☆
DRY BRAKING	★★★★★	NOISE	★★★★☆
HANDLING	★★★★★	SNOW TRACTION	★★★★☆

MILEAGE ★★★★★

Ultra Sport+

Rim	Size	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
17	205/45R17 XL	88	W	7J	560	1235	340	50
	205/50R17 XL	93	W	6 1/2J	650	1433	340	50
	215/45R17 XL	91	W	7J	615	1356	340	50
	215/50R17 XL	95	W	7J	690	1521	340	50
	215/55R17 XL	98	W	7J	750	1653	340	50
	225/45R17 XL	94	W	7 1/2J	670	1477	340	50
	225/50R17 XL	98	W	7J	750	1653	340	50
	225/55R17 XL	101	W	7J	825	1819	340	50
	235/45R17 XL	97	W	8J	730	1609	340	50
	235/55R17	99	W	7 1/2J	775	1709	340	44
18	215/45R18 XL	93	W	7J	650	1433	300	50
	225/40R18 XL	92	W	8J	630	1389	340	50
	225/45R18 XL	95	W	7 1/2J	690	1521	340	50
	225/50R18	95	W	7J	690	1521	340	44
	235/40R18 XL	95	W	8 1/2J	690	1521	300	50
	235/45R18 XL	98	W	8J	750	1653	340	50
	235/50R18 XL	101	W	7 1/2J	825	1819	340	50
	235/55R18 XL	104	W	7 1/2J	900	1984	340	50
	245/40R18 XL	97	W	8 1/2J	730	1609	340	50
	245/45R18 XL	100	W	8J	800	1764	340	50

Ultra Sport+

Rim	Size	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
19	225/45R19 XL	96	W	7 1/2J	710	1565	340	50
	235/35R19 XL	91	W	8 1/2J	615	1356	340	50
	245/35R19 XL	93	W	8 1/2J	650	1433	340	50
	245/40R19 XL	98	W	8 1/2J	750	1653	340	50
	245/45R19 XL	102	W	8J	850	1874	340	50
	255/35R19 XL	96	W	9J	710	1565	340	50
	255/40R19 XL	100	W	9J	800	1764	340	50
	275/35R19 XL	100	W	9 1/2J	800	1764	340	50
20	245/35R20 XL	95	W	8 1/2J	690	1521	340	50
	245/40R20 XL	99	W	8 1/2J	775	1709	340	50
	245/45R20 XL	103	W	8J	875	1929	340	50
	245/50R20	102	W	7 1/2J	850	1874	340	44
	255/35R20 XL	97	W	9J	730	1609	300	50
	255/45R20 XL	105	W	8 1/2J	925	2039	340	50
	275/35R20 XL	102	W	9 1/2J	850	1874	340	50
21	275/40R21 XL	107	Y	9 1/2J	975	2149	340	50
	315/35R21 XL	111	W	11J	1090	2403	340	50
22	275/35R22 XL	104	Y	9 1/2J	900	1984	340	50
	285/35R22 XL	106	W	10J	950	2094	340	50



Ultra High Performance

ULTRA SPORT+

HP010 PLUS

High Performance



Excellent Traction

The optimized profile and enlarged contact patch provide outstanding traction and grip performance



Quiet and Comfortable Ride

The symmetrical tread design ensures a quiet and comfortable ride



Superior Mileage

A high carbon black content in the tread compound improves treadwear and extends tread life



Dry braking

Ride & Comfort

Wet Braking

Noise

On-Center and Off-Center Handling

Active Safety Limit Handling

TEST RESULT

— H BRAND
— LAST GEN
— HP010 PLUS

WET BRAKING	★★★★★	RIDE COMFORT	★★★★★
DRY BRAKING	★★★★★	NOISE	★★★★★
HANDLING	★★★★★	SNOW TRACTION	★★★★★

MILEAGE ★★★★★

High Performance

HP010 PLUS

HP⁰¹⁰ PLUS

Rim	Size	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
14	175/65R14	82	H	5J	475	1047	300	44
	185/65R14	86	H	5 1/2J	530	1168	300	44
	185/70R14	88	T	5 1/2J	560	1235	300	44
	195/70R14	91	T	6J	615	1356	300	44
15	185/60R15	84	H	5 1/2J	500	1102	300	44
	185/65R15	88	H	5 1/2J	560	1235	300	44
	195/60R15	88	H	6J	560	1235	300	44
	195/65R15	91	H	6J	615	1356	300	44
	205/60R15	91	H	6J	615	1356	300	44
	205/65R15	94	H	6J	670	1477	300	44
	215/70R15	98	T	6 1/2J	750	1653	300	44
16	195/55R16	87	H	6J	545	1201	300	44
	205/55R16	91	H	6 1/2J	615	1356	300	44
	205/60R16	92	H	6J	630	1389	300	44
	215/55R16	93	H	7J	650	1433	300	44
	215/60R16	95	V	6 1/2J	690	1521	300	44
	215/65R16	98	H	6 1/2J	750	1653	300	44
	215/70R16	100	T	6 1/2J	800	1764	300	44
	225/65R16	100	H	6 1/2J	800	1764	300	44
	225/60R16	98	H	6 1/2J	750	1653	300	44
	235/60R16	100	H	7J	800	1764	300	44
	235/65R16	103	H	7J	875	1929	300	44
	215/45R17 XL	91	W	7J	615	1356	340	50
17	215/50R17	91	V	7J	615	1356	300	44
	215/55R17	94	V	7J	670	1477	300	44
	215/60R17	96	H	6 1/2J	710	1565	300	44
	215/65R17	99	H	6 1/2J	775	1709	300	44
	225/45R17 XL	94	W	7 1/2J	670	1477	340	50

HP⁰¹⁰ PLUS

Rim	Size	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
17	225/50R17 XL	98	V	7J	750	1653	340	50
	225/55R17	97	V	7J	730	1609	300	44
	225/60R17	99	H	6 1/2J	775	1709	300	44
	225/65R17	102	H	6 1/2J	850	1874	300	44
	235/45R17 XL	97	V	8J	730	1609	340	50
	235/55R17	99	V	7 1/2J	775	1709	300	44
	235/60R17	102	H	7J	850	1874	300	44
	235/65R17	104	H	7J	900	1984	300	44
18	215/55R18 XL	99	H	7J	775	1709	340	50
	225/40R18 XL	92	W	8J	630	1389	340	50
	225/45R18 XL	95	W	7 1/2J	690	1521	340	50
	225/50R18	95	W	7J	690	1521	300	44
	225/55R18	98	H	7J	750	1653	300	44
	225/60R18	100	H	6 1/2J	800	1764	300	44
	235/50R18	97	W	7 1/2J	730	1609	300	44
	235/55R18 XL	104	V	7 1/2J	900	1984	340	50
	235/60R18	103	H	7J	875	1929	300	44
	235/65R18	106	H	7J	950	2094	300	44
	245/40R18 XL	97	W	8 1/2J	730	1609	340	50
	245/45R18 XL	100	W	8J	800	1764	340	50
	245/60R18	105	H	7J	925	2039	300	44
	255/65R18	111	H	7 1/2J	1090	2403	300	44
19	225/55R19	99	V	7J	775	1709	300	44
	225/45R19 XL	96	W	7 1/2J	710	1565	340	50
	235/40R19 XL	96	V	8 1/2J	710	1565	340	50
	235/55R19 XL	105	V	7 1/2J	925	2039	340	50
	245/45R19 XL	102	V	8J	850	1874	340	50
	255/45R19 XL	104	V	8 1/2J	900	1984	340	50
	255/60R19	109	H	7 1/2J	1030	2271	300	44




High Performance

HP⁰¹⁰ Plus

Crosswind HT²

Highway Terrain Tire



Confident Driving on Wet Roads

Four wide circumferential grooves and zigzag sipes significantly enhance water evacuation, ensuring confident driving even in heavy rain



Low Road Noise

The optimized variable pitch design, combined with an optimized pitch sequence and arrangement, reduces road noise



Long-Lasting Performance

The combination of natural rubber and high carbon black content delivers excellent wear and chip resistance



Highway Terrain Tire

WET BRAKING ★★★★★
 DRY BRAKING ★★★★★
 RIDE COMFORT ★★★★★

NOISE ★★★★★
 SNOW TRACTION ★★★★★
 OFF-ROAD TRACTION ★★★★★

MILEAGE ★★★★★

Crosswind HT²

Crosswind HT²

Rim	Size	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
15	235/75R15	105	T	6 1/2J	925	2039	300	44
	215/70R16	100	H	6 1/2J	800	1764	300	44
16	225/70R16	103	T	6 1/2J	875	1929	300	44
	235/70R16	106	T	7J	950	2094	300	44
	245/70R16	107	T	7J	975	2149	300	44
	255/70R16	111	T	7 1/2J	1090	2403	300	44
	265/70R16	112	T	8J	1120	2469	300	44
	265/75R16	116	T	7 1/2J	1250	2756	300	44
	245/75R16	111	T	7J	1090	2403	300	44
	215/65R17	99	T	6 1/2J	775	1709	300	44
17	225/60R17	99	H	6 1/2J	775	1709	300	44
	235/60R17 XL	106	H	7J	950	2094	340	50
	235/65R17	104	T	7J	900	1984	300	44
	235/70R17	107	T	7J	975	2149	300	44
	245/65R17	107	T	7J	975	2149	300	44
	245/70R17	110	T	7J	1060	2337	300	44
	255/65R17	110	T	7 1/2J	1060	2337	300	44
	265/65R17	112	T	8J	1120	2469	300	44
18	225/55R18	98	H	7J	750	1653	300	44
	235/55R18 XL	104	H	7 1/2J	900	1984	340	50
	235/60R18 XL	107	H	7J	975	2149	340	50
	235/65R18	106	H	7J	950	2094	300	44

Crosswind HT²

Rim	Size	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
18	245/60R18	105	H	7J	925	2039	300	44
	255/55R18	105	H	8J	925	2039	300	44
	255/65R18	111	T	7 1/2J	1090	2403	300	44
	255/70R18	113	T	7 1/2J	1150	2535	300	44
	265/65R18	114	T	8J	1180	2601	300	44
	265/70R18	116	T	8J	1250	2756	300	44
	275/65R18	116	T	8J	1250	2756	300	44
19	235/55R19	101	H	7 1/2J	825	1819	300	44
	245/55R19	103	H	7 1/2J	875	1929	300	44
	255/50R19 XL	107	H	8J	975	2149	340	50
	255/60R19	109	H	7 1/2J	1030	2271	300	44
20	235/55R20	102	H	7 1/2J	850	1874	300	44
	245/60R20	107	H	7J	975	2149	300	44
	245/50R20	102	H	7 1/2J	850	1874	300	44
	255/50R20 XL	109	H	8J	1030	2271	340	50
	255/60R20 XL	113	T	8J	1150	2535	340	50
	265/50R20	107	H	8 1/2J	975	2149	300	44
	275/55R20	113	H	8 1/2J	1150	2535	300	44
	275/60R20	115	T	8J	1215	2679	300	44
22	285/45R22	110	H	9 1/2J	1060	2337	300	44



Highway Terrain Tire

Crosswind HT²

TRAILTRAXX

All-Terrain Tire



Outstanding All-Terrain Durability

The high-strength carcass and cut-resistant tread compound help protect the tread and sidewall from impacts and cuts in rough terrain while delivering high mileage



Excellent All-Weather Traction

An innovative tread compound and tread pattern featuring zigzag sipes deliver excellent wet performance and snow traction



All-Terrain Versatility

Optimized pitch arrangement and tread pattern stiffness reduce road noise



All-Terrain Tire



WET BRAKING	★★★★☆	NOISE	★★★★☆
DRY BRAKING	★★★★☆	SNOW TRACTION	★★★★★
RIDE COMFORT	★★★★☆	OFF-ROAD TRACTION	★★★★☆

MILEAGE ★★★★★

TRAILTRAXX

TRAILTRAXX

Rim	Size	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
16	LT225/75R16	115/112	Q	6J	1215/1120	2680/2470	550	80
	LT265/75R16	123/120	Q	71/2J	1550/1400	3415/3085	550	80
	LT245/75R16	120/116	Q	7J	1380/1260	3042/2778	550	80
	265/75R16	116	S	7 1/2J	1250	2756	300	44
	235/70R16	106	S	7J	950	2094	300	44
	LT285/75R16	126/123	Q	8J	1700/1550	3750/3415	550	80
	265/70R16	112	S	8J	1120	2469	300	44
	245/75R16	111	S	7J	1090	2403	300	44
17	285/70R17	116	T	81/2J	1250	2756	300	44
	LT265/70R17	123/120	Q	8J	1550/1400	3415/3085	550	80
	LT245/75R17	121/118	Q	7J	1450/1320	3195/2910	550	80
	265/70R17	115	S	8J	1215	2679	300	44
	LT285/70R17	126/123	Q	81/2J	1700/1550	3750/3415	550	80
	LT315/70R17	126/123	Q	9 1/2J	1700/1550	3750/3415	450	65
	245/65R17	111	H	7J	1090	2403	340	50
	35X12.50R17LT	125	Q	10J	1650	3640	450	65
	265/65R17	116	S	8J	1250	2756	340	50

TRAILTRAXX

Rim	Size	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
18	255/70R18	113	T	7 1/2J	1150	2535	300	44
	LT295/70R18	129/126	Q	8 1/2J	1850/1700	4080/3750	550	80
	275/65R18	116	T	8J	1250	2756	300	44
	265/70R18	116	T	8J	1250	2756	300	44
	LT275/70R18	125/122	Q	8J	1650/1500	3640/3305	550	80
	LT275/65R18	123/120	Q	8J	1550/1400	3415/3085	550	80
	265/60R18	110	T	8J	1060	2337	300	44
	35X12.50R18LT	128	Q	10J	1800	3970	550	80
20	35X12.50R20LT	125	Q	10J	1650	3640	550	80
	275/60R20	115	T	8J	1215	2679	300	44
	LT275/65R20	126/123	Q	8J	1700/1550	3750/3415	550	80
	LT285/55R20	122/119	Q	9J	1500/1360	3305/3000	550	80
	275/55R20	117	S	8 1/2J	1285	2833	340	50
	LT285/60R20	125/122	Q	8 1/2J	1650/1500	3640/3305	550	80
22	33X12.50R20LT	119	Q	10J	1360	3000	550	80
	285/45R22	110	Q	9 1/2J	1060	2337	300	44
	35X12.50R22LT	121	Q	10J	1450	3195	550	80



All-Terrain Tire

TRAILTRAXX

RUGGED TRAXX

Rugged Terrain Tire



Superior Traction

The crisscross and angular block design provides strong traction on muddy and soft surfaces



All-Season Safety

The tread design, combined with an improved compound and zigzag sipes, enhances wet performance and snow traction



Exceptional Durability

The rugged block design handles all types of harsh terrain and weather conditions



Rugged Terrain Tire

RUGGED TRAXX



WET BRAKING	★★★★★	NOISE	★★★★☆
DRY BRAKING	★★★★★	SNOW TRACTION	★★★★★
RIDE COMFORT	★★★★☆	OFF-ROAD TRACTION	★★★★★

MILEAGE ★★★★★

Rugged Traxx

Rim	Size	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
16	265/70R16	112	Q	8J	1120	2469	300	44
	265/75R16	116	Q	7 1/2J	1250	2756	300	44
	LT245/75R16	120/116	Q	7J	1380/1260	3042/2778	550	80
	LT285/75R16	126/123	Q	8J	1700/1550	3750/3415	550	80
	LT265/75R16	123/120	Q	7 1/2J	1550/1400	3415/3085	550	80
17	35X12.50R17LT	128	Q	10J	1800	3970	550	80
	265/70R17	115	Q	8J	1215	2679	300	44
	265/65R17	112	Q	8J	1120	2469	300	44
	LT245/75R17	121/118	Q	7J	1450/1320	3195/2910	550	80
	LT285/70R17	126/123	Q	8 1/2J	1700/1550	3750/3415	550	80
	LT265/70R17	123/120	Q	8J	1550/1400	3415/3085	550	80
18	35X12.50R18LT	128	Q	10J	1800	3970	550	80
	255/70R18	116	T	7 1/2J	1250	2756	340	50
	275/65R18	116	T	8J	1250	2756	340	50

Rugged Traxx

Rim	Size	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
18	265/60R18	114	Q	8J	1180	2601	340	50
	265/70R18	116	S	8J	1250	2756	300	44
	LT275/70R18	125/122	Q	8J	1650/1500	3640/3305	550	80
	LT275/65R18	123/120	Q	8J	1550/1400	3415/3085	550	80
20	35X12.50R20LT	125	Q	10J	1650	3640	550	80
	275/55R20	117	Q	8 1/2J	1285	2833	340	50
	275/60R20	116	T	8J	1250	2756	340	50
	LT305/55R20	121/118	Q	9 1/2J	1450/1320	3195/2910	450	65
	LT275/65R20	126/123	Q	8J	1700/1550	3750/3415	550	80
	LT285/60R20	125/122	Q	8 1/2J	1650/1500	3640/3305	550	80
22	35X12.50R22LT	121	Q	10J	1450	3195	550	80
	37X13.50R22LT	128	Q	11J	1800	3970	550	80
	285/45R22	114	Q	9 1/2J	1180	2601	340	50
24	35X12.50R24LT	116	Q	10 1/2J	1250	2755	550	80



Rugged Terrain Tire

RUGGED TRAXX

Replacement Market Tires Warranty Manual



Warranty Eligibility

This Limited Warranty applies to all qualified replacement-market passenger and light truck tires manufactured by Shandong Linglong Tyre Co., Ltd. and its subsidiaries. This Limited Warranty applies only to the original purchaser and only to tires bearing a complete brand identification and a valid DOT code or barcode. This Limited Warranty is valid only if all of the following conditions are met:

- The tires were manufactured on or after January 1, 2025, and were shipped to North America for sale and use.
- The tire fails due to the workmanship or materials.
- The tire is within the applicable warranty period, and the remaining tread depth is above the Tread Wear Indicator (TWI).

What Is Warranted and for How Long

If a tire covered by this Limited Warranty becomes unserviceable due to a defect in workmanship or materials while the remaining tread depth is above the Tread Wear Indicator (TWI), Linglong will provide warranty coverage in accordance with the terms and conditions of this Limited Warranty.

- The warranty period is six (6) years from the date of purchase or seven (7) years from the date of manufacture, whichever comes first, provided the remaining tread depth is above the Tread Wear Indicator (TWI).
- If a tire fails due to manufacturing defects and meets the warranty terms and conditions, with remaining tread depth above the TWI, a new tire of the same specification will be provided free of charge.

What Is Not Covered

1. Road hazard damage caused by obstacles or debris, including cuts, punctures (whether repairable or not), snags, bruises, tears, abrasions, or impact breaks.
2. Improper or failed repairs.
3. Damage resulting from improper inflation or improper maintenance.
4. Damage caused by improper mounting or dismounting.
5. Mechanical irregularities such as bent wheel assemblies, misalignment worn or faulty components.
6. Damage caused by overinflation, underinflation, overloading, or defective vehicle mechanical conditions.
7. Damage from over-inflation or under-inflation, overloading, defective vehicle mechanical conditions.
8. Non-racing or off-road tires that have been misused or abused in racing or off-road applications.
9. Damage caused by ozone or weather cracking, misuse, abuse, tire modifications, or operation while flat (run-flat damage).
- 10.Any tire from which the DOT identification number and/or brand name has been intentionally removed.
- 11.Tires that have been modified after leaving the factory, including the addition of fillers, sealants, balancing compounds, or external tire treatments. If any added material is determined to have caused the failure, the tire will not be eligible for warranty coverage.
- 12.Abnormal tread wear resulting from improper installation, wheel misalignment, tire/wheel assembly imbalance, etc.
- 13.Vehicles or tires operated beyond their rated load capacity.
- 14.Additional monetary loss, such as damage of the vehicle or time, etc.

Road Hazard Warranty

If a tire becomes unserviceable due to a non-repairable road hazard, it must meet the following eligibility requirements:

- The tire must be within one (1) year of the date of purchase. The original proof of purchase must be provided.
- For eligible tires, compensation will be equal to 50% of the total FOB tire price plus freight.

Treadwear Mileage Warranty

If an eligible tire wears evenly to the Tread Wear Indicator (TWI) before reaching the warranted mileage, under normal passenger vehicle use and within the applicable Limited Warranty period. The unused service will be subsidized on a pro-rata basis to purchase a new tire. To submit a claim, installation record, tire rotation record, tire rotation records, and tire removal record must be provided with the claimed tire.

- Tires must be rotated every 6,000 to 8,000 miles (10,000 to 13,000 km), or sooner.
- This warranty does not apply to original equipment (OE) tires.
- The Treadwear Mileage Warranty applies only to the original purchaser and owner of the tires.
- This Mileage Warranty does not apply to tires used in commercial applications, including but not limited to law enforcement vehicles, taxi services, courier services, delivery fleets, or other commercial uses.
- To qualify for this warranty, tires must show even tread wear, with no more than a 2/32" difference in tread depth across the tire tread.

Mileage Warranty Product List:

Product Line	Mileage Warranty
ULTRA SPORT +	50,000 miles (80,000 km)
HP ^{®10} PLUS	55,000 miles (90,000 km)
CROSSWIND HT ²	55,000 miles (90,000 km)
TRAILTRAXX	60,000 miles (100,000 km)
RUGGED TRAXX	50,000 miles (80,000 km)

90-DAY Customer Satisfaction Trial

LingLong offers a 90 Day Free Trial as the following :

- Applies to passenger tires only (Excludes commercial, light truck (LT), racing, and other specialty tires).
- This Satisfaction Guarantee applies only to the original purchaser who purchases at least four (4) new passenger tires in a single transaction. It does not apply to replacement tires provided under this guarantee.
- This guarantee does not apply to tires that have been intentionally damaged or damaged due to misuse, abuse, or improper use.
- How do you return your tires during the trial period?
 - A.Within the applicable trial period from the date of purchase, you must return your tires to the tire dealer where you purchased your tires.
 - B.Present the original sales receipt or other proof of purchase.
 - C.Provide the reason for your dissatisfaction (such as appearance, ride comfort, or handling, etc.).

To Make a Claim Under This Limited Warranty

- Present your tires and the original proof of purchase to the original place of purchase or any authorized Company dealer.
- Complete and sign the Warranty Claim Adjustment Form, keep a copy for your records, and leave the tire with the dealer for warranty claim processing;

Owner’s Responsibilities

- At the time of purchase, tires must be properly installed with recommended inflation and balanced. Observe rotation and alignment regularly according to recommendations.
- To submit a warranty claim, contact the original place of purchase or any authorized Company dealer.
- The owner is responsible for all service charges and applicable taxes.
- A copy of the original proof of purchase must be submitted to support the warranty claim.

Tire Safety and Maintenance

Tire failure can result in serious property damage and/or personal injury. To help reduce these risks, we recommend the following safety practices:

- 1.Maintain proper tire inflation pressure. Do not underinflate or overinflate your tires. Always maintain inflation pressure according to the vehicle manufacturer’s recommendations or the tire manufacturer’s specifications.
- 2.Check wheel alignment and tire balance regularly to help ensure proper handling, performance, and even tread wear.
- 3.Do not overload your vehicle. Refer to the tire sidewall markings for the tire’s maximum load-carrying capacity.
- 4.Avoid excessive tire spinning & impacts with curbs, potholes, obstacles, pavement edges.
- 5.Never drive on worn-out (bald) tires. By law, tires must be replaced when the tread reaches the Tread Wear Indicator (TWI).
- 6.Inspect your tires regularly for signs of damage, including cuts, abrasions, punctures, foreign objects, separations, or bulges. If damage is found, replace the tire with the spare tire (if available) and consult an authorized tire dealer.
- 7.Do not exceed posted speed limits or the maximum speed rating specified for the tire.
- 8.To promote even wear and maximize tread life, rotate your tires at least every 6,000 miles (10,000 km) or according to the vehicle manufacturer’s recommendations.

Exclusions, Limitations, and Legal Rights

No representative, dealer, or distributor is authorized to make any representation, promise, or agreement on behalf of Linglong, except as expressly stated in this warranty document. Any tire, regardless of construction quality, may fail in service or otherwise become unserviceable due to conditions beyond the manufacturer’s control. This warranty does not constitute a representation that tire failure will not occur under any circumstances.

DISCLAIMER: This warranty is provided in lieu of all other warranties and representations, express or implied. Linglong expressly disclaims all implied warranties, including but not limited to the implied warranties of merchantability and fitness for a particular purpose. No other warranty, guarantee, or representation of any kind shall be deemed to exist or arise by operation of law.

LIMITATION OF DAMAGES: Under no circumstances shall Linglong be liable for any indirect, special, incidental, consequential, or punitive damages, including but not limited to loss of profits, business interruption, loss of reputation or goodwill, or costs related to replacement transportation or other related expenses. Some states and provinces do not allow the exclusion or limitation of incidental or consequential damages; therefore, certain portions of this limitation may not apply in specific jurisdictions.

This warranty establishes specific legal rights and obligations. Additional rights may apply depending on the applicable state or provincial laws.



